



# اماکن صنعت

اماکن خود را با امنیت  
ترک کنید

# Tiandy

آنالیزهای هوشمند دوربین

## TC-NC252S



**Loitering**

آلارم در حال پرسه زنی

آلارم ازدحام جمعیت

**Crowd**

آلارم دویدن در یک ناحیه

**Running**

آلارم ورود به یک ناحیه

**Perimeter**

**Tripwire**

آلارم عبور از خط مجازی

# AKANSANAT





تشخیص  
ورود به ناحیه  
غیر مجاز

تشخیص  
و هشدار  
مفقود شدن اشیاء  
محدوده دید دوربین

تشخیص  
و هشدار  
تغییر محدوده  
دید دوربین

تشخیص  
تجمعات

مدل	مشخصات فنی	قیمت (ریال)
1 AC-DH1050-E	<p>1/2.5" Image Sensor 3.6mm 5 MegaPixel Fixed lens Resolution 2608 (H) × 1952(V), 5.0MP Mechanical ICR, 2DNR , AWB, BLC 40~45 m IR Board , 48 IR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>	
2 AC-DH1020-EL	<p>1/2.9" Image Sensor 3.6mm 2 MegaPixel Fixed lens 1920 (H) × 1080 (V) Resolution , 2 MP Mechanical ICR , 3DNR , DWDR , AWB, BLC OSD Menu by UTC (output 4-in-1) 40~45 m IR Board , 48 IR LED IP66, Metal Case</p>	
3 AC-DH2020N-EL	<p>1/2.9" Image Sensor 3.6mm 2 MegaPixel Fixed lens 1920 (H) × 1080 (V) Resolution , 2 MP Mechanical ICR , 3DNR , DWDR , AWB, BLC 30~35 m IR Board, 36 IR LED OSD Menu by UTC (output 4-in-1) IP66</p>	
4 AC-BH1320-EL NEW Product	<p>1/2.9" Image Sensor 3.6mm 2 MegaPixel Fixed lens 1920 (H) × 1080 (V) Resolution , 2 MP Mechanical ICR , 3DNR , DWDR , AWB, BLC 35~40 m IR Board, High power LED OSD Menu by UTC (output 4-in-1) IP66</p>	
5 AC-BH1350-E NEW Product	<p>1/2.5" Image Sensor 3.6mm 5 MegaPixel Fixed lens Resolution 2608 (H) × 1952(V), 5.0MP Mechanical ICR, 2DNR , AWB, BLC 35~40 m IR Board, High power LED OSD Menu by UTC(output 4-in-1) IP66</p>	
6 AC-BH4320-EL	<p>1/2.9" Image Sensor 3.6mm 2 MegaPixel Fixed lens 1920 (H) × 1080 (V) Resolution , 2 MP Mechanical ICR , 3DNR , DWDR , AWB, BLC 25~30 m IR Board, 6 Mini Array OSD Menu by UTC (output 4-in-1) IP66</p>	
7 AC-BH5020N-EL	<p>1/2.9" Image Sensor 3.6mm 2 MegaPixel Fixed lens 1920 (H) × 1080 (V) Resolution , 2 MP Mechanical ICR, DWDR , 3DNR , AWB, BLC 30~35 m IR Board , 30 IR LED OSD Menu by UTC(output 4-in-1) IP66</p>	



مدل	مشخصات فنی	قیمت (ریال)
8 AC-BH5320-EL	<p>1/2.9" Image Sensor  3.6mm 2 MegaPixel Fixed lens  1920 (H) × 1080 (V) Resolution , 2 MP  Mechanical ICR , 3DNR , DWDR , AWB, BLC  25~30 m IR Board, 6 Mini Array  OSD Menu by UTC (output 4-in-1)  IP66</p>	
9 AC-BH6320-EL	<p>1/2.9" Image Sensor  3.6mm 2 MegaPixel Fixed lens  1920 (H) × 1080 (V) Resolution , 2 MP  Mechanical ICR , 3DNR , DWDR , AWB, BLC  25~30 m IR Board, 6 Mini Array  OSD Menu by UTC (output 4-in-1)  IP66</p>	
10 AC-BH6520-EL	<p>1/2.9" Image Sensor  3.6mm 2 MegaPixel Fixed lens  1920 (H) × 1080 (V) Resolution , 2 MP  Mechanical ICR , 3DNR , DWDR , AWB, BLC  35~40 m IR Board, 42 IR LED  OSD Menu by UTC (output 4-in-1)  IP66</p>	
11 AC-BH9120-EL NEW Product	<p>1/2.9" Image Sensor  3.6mm 2 MegaPixel Fixed lens  1920 (H) × 1080 (V) Resolution , 2 MP  Mechanical ICR, DWDR , 3DNR , AWB, BLC  60 m IR Board , 2 Array LED  OSD Menu by UTC (output 4-in-1)  IP66</p>	
12 AC-BH9020-EL NEW Product	<p>1/2.9" Image Sensor  3.6mm 2 MegaPixel Fixed lens  1920 (H) × 1080 (V) Resolution , 2 MP  Mechanical ICR, DWDR , 3DNR , AWB, BLC  40 m IR Board , 1 Array LED  OSD Menu by UTC(output 4-in-1)  IP66</p>	
13 AC-BH7020N-E	<p>1/2.9" Image Sensor  3.6mm 2 MegaPixel Fixed lens  1932 (H) × 1088 (V) Resolution , 2.1 MP  Mechanical ICR , 3DNR , DWDR , AWB, BLC  OSD Menu by UTC(output 4-in-1)  40~50 m IR Board, High power IR LED  IP66</p>	
14 AC-BH7050-E	<p>1/2.5" Image Sensor  3.6mm 5 MegaPixel Fixed lens  Resolution 2608 (H) × 1952(V), 5.0MP  Mechanical ICR, 2DNR , AWB, BLC  40~50 m IR Board ,High power IR LED  OSD Menu by UTC(output 4-in-1)  IP66</p>	

مدل	مشخصات فنی	قیمت (ریال)
15 AC-BH7150V-E NEW Product	<p>1/2.5" Image Sensor 2.8~12 mm 5 MegaPixel Varifocal lens Resolution 2608 (H) × 1952(V), <b>5.0MP</b> Mechanical ICR, 2DNR , AWB, BLC OSD Menu by UTC(output 4-in-1) 50~60 m IR Board , 48 IR LED IP66</p>	
16 AC-BH7120V-E	<p>1/2.9" Image Sensor 2.8~12mm 2 MegaPixel Varifocal lens Resolution 1932 (H) × 1088 (V), 2.1MP Mechanical ICR, DWDR , 3DNR , AWB, BLC 50~60 m IR Board , 48 IR LED OSD Menu by UTC(output 4-in-1) IP66</p>	
17 AC-BH8050-E	<p>1/2.5" Image Sensor 3.6mm 5 MegaPixel Fixed lens Resolution 2608 (H) × 1952(V), 5.0MP Mechanical ICR, 2DNR , AWB, BLC 50~60m IR Board , high power IR LED OSD Menu by UTC(output 4-in-1) IP66</p>	
18 AAD-7104X-A1	<p>4CH AHD <b>H.265 5MP-N</b> None-Real Time DVR 4CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity: 4*5MP-N@20fps/4*4MP-N@25fps/4*1080P@25fps Code Capacity: 4*5MP-N@8fps/4*4MP-N@15fps/4*1080P@18fps/4*1080N@25fps 4CH Playback <b>Support real-time face detection, Face list</b> <b>Pentabrid</b> (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 1CH Audio In 2*USB 2.0 1*10/100 Mbps LAN Interface P2P support IOS-Andriod Mobile APP &amp; CMS PC Software</p>	
19 AAD-7108X-A1	<p>8CH AHD <b>H.265 5MP-N</b> DVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity: 8*5MP-N@12fps/8*4MP-N@15fps/8*1080N@25fps Code Capacity: 8*5MP-N@6fps/8*4MP-N@8fps/8*1080P@8fps/8*1080N@15fps 8CH Playback: 4ch main stream/8ch sub-stream <b>Support real-time face detection, Face list, Face playback</b> <b>Pentabrid</b> (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 1CH Audio In 2*USB 2.0 1*10/100 Mbps LAN Interface P2P support</p>	



## TC-NC23M

2MP IR Bullet Camera  
1/2.7" 2Megapixel progressive CMOS  
8-12mm Motorized lens, Angle of View:  
4.7°~36.9°  
25fps@2M(1920×1080)  
S+265/H.264 triple-stream encoding  
WDR(100dB), Day/Night(ICR), 3DNR, AGC,  
HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/alarm times count)  
1/1 Audio In/Out, 1/0 Alarm In/Out  
Micro SD card 128GB  
Max IR LEDs Length 30~50m, Smart IR  
IP67, PoE



## Starlight

## TC-NC23MS

2MP Starlight Motorized IR Bullet Camera  
1/2.8" 2Megapixel progressive CMOS  
2.8-12mm Motorized lens, Angle of  
View:92°~38.6°  
25fps@2M (1920\*1080)  
S+265/H.264/MJPEG triple-stream encoding  
Starlight Ultra Low Light 0.002lux  
WDR(140dB), Day/Night(ICR), 3DNR, AGC,  
HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal  
Detection)  
1/1 Audio in/Out, 2/1 Alarm in/Out  
RS485, USB, Micro SD card 128GB  
Max IR LEDs Length 30-50m, Smart IR  
IP67, PoE



## TC-NC43M

2MP H.265 Motorized IR Bullet Camera  
1/3" 4Megapixel progressive CMOS  
8-12mm Motorized lens, Angle of  
View:90.8°~32.1°  
25fps@4M(2560X1440)  
S+265/H.264/MJPEG triple-stream encoding  
WDR(120dB), Day/Night(ICR), 3DNR, AGC,  
HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal  
Detection)  
1/1 Audio in/Out, 2/1 Audio in/Out  
RS485, USB, Micro SD card 128GB  
Max IR LEDs Length 30~50m, Smart IR  
IP67, PoE



31,500,000

## TC-C32HN

2MP IR Bullet Camera  
1/2.9" 2Megapixel progressive CMOS  
2.8mm fixed lens  
30fps@2M (1920\*1080)  
S+265/H.265/H.264/M-JPEG dual-stream  
encoding  
WDR(100db), Day/Night(ICR), 3DNR, HLC  
Smart Defog  
Max IR LEDs Length 30m, Smart IR  
PoE, IP66



## TC-C32KN

2MP Vandal Proof Mini IR Dome Camera  
1/2.7" 2Megapixel progressive CMOS  
8mm Fixed lens, Angle of View: 109.3°  
25fps@2M(1920X1080)  
S+265/H.264/MJPEG Triple-stream encoding  
WDR(100dB), Day/Night(ICR), 3DNR, HLC, BLC  
Smart Defog, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Video  
Abnormal Detection)  
Built in Mic, 1CH Audio In, Micro SD card  
128GB  
Max IR LEDs Length 20m, Smart IR  
Flexible Free Design  
IP66,IK10, PoE



## TC-NC24M

2MP Vandal Proof IR Dome Camera  
1/2.7" 2Megapixel progressive CMOS  
2.8-12mm Motorized lens, Angle of View:  
101°~38°  
25fps@2M(1920×1080)  
S+265/H.264 triple-stream encoding  
WDR(100dB), Day/Night(ICR), 3DNR, AGC,  
HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/alarm times count)  
1/1 Audio In/Out, 2/2 Alarm In/Out  
Built-In Mic  
Micro SD card 128GB  
Max IR LEDs Length 20~30m, Smart IR  
IP66, IK10, PoE



### TC-C32GN

2MP IR Bullet Camera  
1/2.9" 2Megapixel progressive CMOS  
4mm fixed lens  
30fps@2M (1920\*1080)  
S+265/H.265/H.264/M-JPEG dual-stream encoding  
WDR(100db), Day/Night(ICR), 3DNR, HLC  
Smart Defog  
Max IR LEDs Length 50m, Smart IR  
PoE, IP67



### Super Starlight

2MP IR Bullet Camera  
1/2.8" 2Megapixel progressive CMOS  
4mm fixed lens  
30fps@2M (1920\*1080)  
S+265/H.265/H.264/M-JPEG dual-stream encoding  
Starlight Ultra Low Light 0.0008 lux  
WDR(120db), Day/Night(ICR), 3DNR, HLC  
Smart Defog  
Max IR LEDs Length 50m, Smart IR  
PoE, IP67



### TC-C32GP

### Starlight

### TC-NC514S

5MP Starlight IR Bullet Camera  
1/2.8" 5Megapixel progressive CMOS  
4mm fixed lens  
20fps@5M (2560\*1920)  
S+265/H.264/M-JPEG dual-stream encoding  
WDR(120db), Day/Night(ICR), 3DNR, HLC  
VCA (Tripwire/Double  
Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal  
Detection)  
Smart Defog  
Micro SD card 128GB  
Max IR LEDs Length 20~30m, Smart IR  
PoE, IP67



### TC-C32JN

2MP IR Bullet Camera  
1/2.9" 2Megapixel progressive CMOS  
4mm fixed lens  
30fps@2M (1920\*1080)  
S+265/H.265/H.264/M-JPEG dual-stream encoding  
WDR(100db), Day/Night(ICR), 3DNR, HLC  
Smart Defog  
Max IR LEDs Length 50m, Smart IR  
PoE, IP67



### Super Starlight

### TC-NC294XG + Bracket

2MP Super Starlight EXIR Bullet Camera  
1/2.7" 2Megapixel progressive CMOS  
4mm fixed lens, Angle of View: 90°  
25fps@2M (1920\*1080)  
S+265/H.264/MJPEG Encoding  
Starlight Ultra Low Light 0.0004 lux, IR Free  
Design  
WDR(140dB), Day/Night(ICR), 3DNR, AGC, HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal  
Detection)  
1/1 Audio In, 1 Alarm In  
Micro SD card 128GB  
IP67, PoE



### TC-NC414

4MP H.265 Mini IR Bullet Camera  
1/3" 4Megapixel progressive CMOS  
4mm fixed lens, Angle of View: 82.7°  
25fps@4M(2560\*1440)  
S+265/H.264 triple-stream encoding  
WDR(120dB), Day/Night(ICR), 3DNR, AGC, HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double  
Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal  
Detection)  
Micro SD card 128GB  
Max IR LEDs Length 20~30m, Smart IR  
Cable Free Design  
IP67, PoE





## Starlight

## TC-NC552S

5MP Starlight Vandalproof Mini IR Dome Camera  
1/2.8" 5Megapixel progressive CMOS  
2.8mm Fixed lens  
20fps@5M()  
S+265/H.264/M-JPEG triple-stream encoding  
WDR(100dB), Day/Night(ICR), 3DNR, AGC, HLC  
VCA (Tripwire/Double Tripwire/Perimeter/Object  
Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal Detection)  
Smart Defog, EIS, ROI  
Built in Mic  
1CH Audio In  
Micro SD card 128GB  
Max IR LEDs Length 20m, Smart IR  
Cable Free Design  
IP66, IK10, PoE



## TC-NC452

4MP H.265 Vandal proof Mini IR Dome Camera  
1/3" 4Megapixel progressive CMOS  
2.8mm Fixed lens, Angle of View: 99°  
25fps@4M(2560X1440)  
S+265/H.264/MJPEG Triple-stream encoding  
WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double Tripwire/Perimeter/Object  
Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio Abnormal Detection/Video  
Abnormal Detection)  
Built in Mic  
1CH Audio In  
Micro SD card 128GB  
Max IR LEDs Length 20m, Smart IR  
Cable Free Design  
IP67, IK10, PoE



## TC-NC44M

4MP H.265 Vandal proof Motorized IR Dome Camera  
1/3" 4Megapixel progressive CMOS  
2.8-12mm Motorized lens, Angle of View: 90.8°~32.1°  
25fps@4M(2560X1440)  
S+265/H.264/MJPEG Triple-stream encoding  
WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, HLC  
Smart Defog, EIS, ROI  
VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio Abnormal Detection/Video  
Abnormal Detection)  
Smart Defog, EIS, ROI  
Built in Mic  
1/1CH Audio In/Out, 2/1 Alarm In/Out  
Micro SD card 128GB  
Max IR LEDs Length 30m, Smart IR  
IP67, IK10, PoE



## Starlight

## TC-NH6220IE-CP

2MP 20x Starlight POE IR PTZ  
1/2.8" 2Megapixel CMOS  
S+265/H.264/MJPEG Triple-streams encoding  
Max.25fps@2M(1920\*1080)  
5.2mm~98mm 20x optical zoom  
Starlight Ultra Low Light 0.002lux  
Max 400°/s pan speed, 16°~90° Tilt Angle, 360°  
endless pan rotation  
WDR(140dB), ICR, 3D-DNR, HLC, BLC, AGC, AWB, Defog  
VCA(Tripwire/Double Tripwire/Perimeter/Object Abandon/Object  
Lost/Running/Loitering/Parking/Crowd/Audio  
Abnormal Detection/Video Abnormal Detection)  
Up to 500 presets, 8 Cruise, 8 pattern, Auto scan, Auto Pan  
Built in Mic  
Alarm 1/1 in/out  
Audio 1/1 in/out  
Micro SD card 128GB  
IR Distance up to 100m  
IP66, PoE+



## Starlight

## TC-H326S Spec:33X/I/E/A

2MP 33x Starlight PoE IR PTZ  
1/2.8" 2Megapixel CMOS  
S+265/H.265/H.264/MJPEG Triple-streams encoding  
Max.30fps@2M(1920\*1080)  
4.6mm~152mm 33x optical zoom  
Starlight Ultra Low Light 0.002 lux  
Max 360°/s pan speed, 16°~90° Tilt Angle, 360°  
endless pan rotation  
WDR(140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC, AGC, AWB  
Smart Defog, ROI  
Auto Tracking  
VCA (Tripwire/Double Tripwire/Perimeter/Object  
Abandon/Object  
Lost/Running/Loitering/Parking/Audio  
Abnormal Detection/Video Abnormal Detection/Heatmap/Auto Tracking)  
Up to 500 presets, 16 Cruise, 8 pattern  
Alarm 1/1 in/out, Audio 1/1 in/out  
Micro SD card 128GB  
IR Distance up to 150m  
IP66



**Starlight****TC-NH3204IE**

2MP 4x Starlight Mini EW IR POE PTZ  
 1/2.8" 2Megapixel CMOS  
 S+265/H.264/MJPEG Triple-streams encoding  
 Max.25fps@2M(1920\*1080)  
 2.8mm~12mm 4x optical zoom  
 Starlight Ultra Low Light 0.002lux  
 Max 60°/s pan speed, 2~90° Tilt Angle,  
 355° endless pan rotation  
 WDR(140dB), ICR, 3D-DNR, HLC, BLC, AGC, AWB  
 Support Defog, ROI  
 \*Early Warning (EW)  
 IR LED + White Light + Speaker  
 VCA (Tripwire/Double  
 Tripwire/Perimeter/Object  
 Abandon/Object  
 Lost/Running/Loitering/Parking/Early  
 Warning/Crowd/Audio Abnormal  
 Detection/Video Abnormal Detection)  
 Up to 500 presets, 8 Cruise, 8 pattern  
 Built-In Mic, Built-In Speaker  
 Alarm 2/1 in/out, Audio 1/0 in/out  
 Micro SD card 128GB  
 IR Distance up to 50m  
 IP65, PoE

**Super Starlight****TC-NH6244ISA-G**

2MP 44x Super Starlight AEW IR PTZ  
 1/1.8" 2Megapixel CMOS  
 H.265/H.264/MJPEG Triple-streams encoding  
 Max.60fps@2M(1920\*1080)  
 4.9mm~216mm 44x optical zoom  
 Super Starlight Ultra Low Light 0.0004 lux  
 Max 400°/s pan speed, 16~90° Tilt Angle,  
 360° endless pan rotation  
 WDR(140dB), ICR, 3D-DNR, HLC, BLC, AGC, AWB  
 Support Defog, ROI, Wiper  
 \*Auto Tracking Early Warning (AEW)  
 IR LED + White Light + Green Laser  
 VCA (Tripwire/Double  
 Tripwire/Perimeter/Object  
 Abandon/Object  
 Lost/Running/Loitering/Parking/Early  
 Warning/Crowd/Audio Abnormal  
 Detection/Video Abnormal Detection/Face  
 Detection/People Counting/on duty  
 Detection/Auto Tracking)  
 Up to 500 presets, 8 Cruise, 8 pattern  
 Built-In Mic, Built-In Speaker  
 Alarm 8/2 in/out, Audio 1/1 in/out  
 RS485  
 Micro SD card 128GB  
 IR Distance up to 200m  
 IP66



Call

**TC-NR5005M7-S1-C**

5 CH 1HDD 1U NVR  
 5 IP camera input  
 S+265/H.264 codec decoding  
 Max 40/40 Mbps incoming/Outgoing  
 bandwidth  
 Up to 5M Resolution Recording  
 Support 5-ch Intelligent Analysis  
 Process(VCA)  
 Support N+1 Hot Standby Function  
 Support ANR Function  
 HDMI/VGA simultaneous video output  
 Max output Resolution 1920x1080  
 Support 1 SATA HDD up to 8TB  
 2 USB Ports  
 1\*10/100 Mbps Network Card  
 P2P support

**TC-NR5010M7-S1-C**

10CH 1HDD 1U NVR  
 10 channel IP camera input  
 S+265/H.264 codec decoding  
 Max 40/40 Mbps incoming/Outgoing  
 bandwidth  
 Up to 5M Resolution for Preview  
 Support 10-ch Intelligent Analysis  
 Process(VCA)  
 Support N+1 Hot Standby Function  
 Support ANR Function  
 HDMI/VGA simultaneous video output  
 Max output Resolution 1920x1080  
 Support 1 SATA HDD up to 8TB  
 2 USB Ports  
 1\*10/100 Mbps Network Card  
 P2P support

**TC-R3110**

10CH 1HDD 1U NVR  
 10 channel IP camera input  
 S+265/H.264 codec decoding  
 Max 40/40 Mbps incoming/Outgoing  
 bandwidth  
 Up to 5MP Resolution Recording  
 Support 10-ch Intelligent Analysis  
 Process(VCA)  
 Plug in free  
 Support ANR Function  
 HDMI/VGA simultaneous video output  
 Max output Resolution 1920x1080  
 Support 1 SATA HDD up to 10TB  
 2 USB Ports  
 1\*10/100 Mbps Network Card  
 P2P support

**TC-R3120**

20CH 1HDD 1U NVR  
 20 channel IP camera input  
 S+265/H.264 codec decoding  
 Max 80/80 Mbps incoming/Outgoing  
 bandwidth  
 Up to 4K Resolution for Preview  
 Support 20-ch Intelligent Analysis  
 Process(VCA)  
 Plug in free  
 Support ANR Function  
 HDMI/VGA simultaneous video output  
 Max output Resolution 4K  
 Support 1 SATA HDD up to 10TB  
 2 USB Ports  
 1\*10/100 Mbps Network Card  
 P2P support

